THATCHER COMPANY OF CALIFORNIA, INC.

8625 Unsworth Avenue, Sacramento, CA 95828



Phone (916) 389-2517 Fax (916) 389-2516

February 17, 2023

AFFIDAVIT OF COMPLIANCE

Aluminum Sulfate

This affidavit certifies and warrants the aluminum sulfate to be delivered to the Bay Area Chemical Consortium Agencies by Thatcher Company of California, Inc. fully complies with A.W.W.A. Specifications and ANSI/NSF Standard 60.

Scott K. Sorensen

President

ATTACHMENT 1

General Manager: Phillip Belden

Phone Number (702) 219-2372

E-mail Address: philip.belden@tchem.com

Market Analyst: Zach Brackus

Phone Number: (800) 375-7758 ext. 1417

E-mail Address: <u>zach.brackus@tchem.com</u>



Applicant: Thatcher Group, Inc. Trade Name: Aluminum Sulfate
Product: Aluminum Sulfate

Manufacturer: Thatcher Co of California, Inc.

Method Name	Analyte Name	Result	Normalized Result	Units	Notes
Regulated Metals - RM60	Antimony	< 0.3	< 0.03	μg/L	
Regulated Metals - RM60	Arsenic	< 0.3	< 0.03	μg/L	
Regulated Metals - RM60	Barium	91	9.1	μg/L	
Regulated Metals - RM60	Beryllium	< 0.15	< 0.015	μg/L	
Regulated Metals - RM60	Cadmium	< 0.3	< 0.03	μg/L	
Regulated Metals - RM60	Chromium	< 1.0	< 0.1	μg/L	
Regulated Metals - RM60	Copper	< 10	< 1	μg/L	
Regulated Metals - RM60	Lead	< 0.3	< 0.03	μg/L	
Regulated Metals - RM60	Selenium	2.0	0.2	μg/L	
Regulated Metals - RM60	Thallium	< 0.15	< 0.015	μg/L	
Mercury - RM60	Mercury	< 0.1	< 0.01		
BNAs	Acenaphthene	< 0.4	< 0.04		
BNAs	Acenaphthylene	< 0.4	< 0.04		
BNAs	Acetophenone	< 0.6	< 0.06		
BNAs	Anthracene	< 0.2	< 0.02		
BNAs	Benzo(a)anthracene	< 0.4	< 0.04		
BNAs	Benzo(b)fluoranthene	< 0.2	< 0.02	μg/L	
BNAs	Benzo(k)fluoranthene	< 0.2	< 0.02	µg/L	
BNAs	Benzo(g,h,i)perylene	< 0.6	< 0.06		
BNAs	Benzo(a)pyrene	< 0.2	< 0.02	13.	
BNAs	Benzothiazole	< 1.0	< 0.1	μg/L	
BNAs	Butylbenzylphthalate	< 1.0	< 0.1	μg/L	
BNAs	4-tert-Butylphenol	< 2.0	< 0.1	μg/L	
BNAs	4-Chloro-3-methylphenol	< 1.0	< 0.2	μg/L μg/L	
BNAs	2-Chlorophenol	< 1.0	< 0.1		
BNAs	_			, ,	
	Chrysene	< 0.3	< 0.03	, ,	
BNAs	Dibenzo(a,h)anthracene	< 0.2	< 0.02		
BNAs	Di-n-butylphthalate	< 2.0	< 0.2		
BNAs	3,3'-Dichlorobenzidine	< 0.5	< 0.05		
BNAs	2,4-Dichlorophenol	< 1.0	< 0.1	, ,	
BNAs	Di(2-ethylhexyl)adipate	< 0.5	< 0.05	, ,	
BNAs	Di(2-ethylhexyl)phthalate	< 0.60	< 0.06		
BNAs	Diethylphthalate	< 1.0	< 0.1	μg/L	
BNAs	2,4-Dimethylphenol	< 2.0	< 0.2		
BNAs	Dimethylphthalate	< 1.0	< 0.1	, ,	
BNAs	2,4-Dinitrophenol	< 1.0	< 0.1	, ,	
BNAs	Di-n-octylphthalate	< 1.0	< 0.1		
BNAs	Diphenylamine	< 0.3	< 0.03	μg/L	
BNAs	2,6-Di-tert-butyl-4- methoxyphenol	< 2.0	< 0.2	μg/L	
BNAs	Fluoranthene	< 0.2	< 0.02	μg/L	
BNAs	Fluorene	< 0.4	< 0.04	μg/L	
BNAs	Indeno(1,2,3-cd)pyrene	< 0.2	< 0.02		
BNAs	Isophorone	< 0.5	< 0.05	μg/L	
BNAs	2-Methyl-4,6-dinitrophenol	< 1.0	< 0.1		
BNAs	2-Methylnaphthalene	< 0.4	< 0.04	μg/L	
BNAs	2-Methylphenol	< 1.0	< 0.1	μg/L	
BNAs	4-Methylphenol	< 1.0	< 0.1	μg/L	
BNAs	Naphthalene	< 0.5	< 0.05		
BNAs	2-Nitrophenol	< 1.0	< 0.1		
BNAs	4-Nitrophenol	< 1.0	< 0.1	μg/L	
	N-Nitrosodi-N-butylamine				
BNAs	(NDBA)	< 0.2	< 0.02	μg/L	

File No.: MH17003

Project No.: F178695

Normalization Factor: 0.1



Applicant: Thatcher Group, Inc. Trade Name: Aluminum Sulfate Product: Aluminum Sulfate

 $\mbox{\tt Manufacturer:} \begin{array}{l} \mbox{\tt Thatcher Co of California,} \\ \mbox{\tt Inc.} \end{array}$

Normalized Method Name Analyte Name Result Units Notes Result N-Nitrosodi-N-propylamine BNAs < 0.2 < 0.02 μg/L (NDPA) BNAs Pentachlorophenol < 0.5 < 0.05 μg/L < 0.02 Phenanthrene < 0.2 BNAs $\mu g/L$ < 0.05 < 0.5 BNAs Phenol $\mu g/L$ < 0.06 BNAs 2-Phenyl-2-propanol < 0.6 μg/L < 0.02 Phenyl sulfone < 0.2 BNAs μg/L < 0.06 BNAs Pyrene < 0.6 μg/L BNAs 2,4,6-Trichlorophenol < 1.0 < 0.1 μg/L BNAs Bisphenol A propoxylate < 5.0 < 0.5 $\mu g/L$ < 5.0 < 0.5 BNAs Caprolactam μg/L < 3.0 BNAs 2,4-Dimethylquinoline < 0.3 μg/L < 0.3 BNAs 2,6-Dimethylquinoline < 3.0 μg/L BNAs Quinoline < 3.0 < 0.3 μg/L BNAs Bisphenol A < 5.0 $< 0.5 \mu g/L$ 1,2-Dihydro-2,2,4-BNAs < 2.0 < 0.2 μg/L trimethylquinoline BNAs 2,3,4-Trimethylquinoline < 2.0 < 0.2 $\mu g/L$ BNAs 2,4,6-Trimethylquinoline < 2.0 < 0.2 μg/L

File No.: MH17003

Project No.: F178695

Normalization Factor: 0.1



Max

FDPH.MH17003 - Drinking Water Treatment Chemicals

Drinking Water Treatment Chemicals

Thatcher Group, Inc. MH17003

1905 FORTUNE RD PO BOX 27407 SALT LAKE CITY, UT 84127-0407 United States

NSF/ANSI 60

Plant at: Thatcher Company of California, Inc., Sacramento, CA

Trade Dsg	Conditions of Acceptability	Category	Use Level (mg/L)
Aluminum Sulfate [*Al]	[Al]	Coagulation and Flocculation Chemicals	150
Aries 293	-	Coagulation and Flocculation Chemicals	250
Ferric Chloride	-	Coagulation and Flocculation Chemicals	250
Poly Phosphate Ortho Phosphate Blends	-	Coagulation and Flocculation Chemicals	26
T-Floc B-135	[Al]	Coagulation and Flocculation Chemicals	250
T-Floc B-41	[AI], [PA]	Coagulation and Flocculation Chemicals	250
Alum, Acidified X [*Al]	-	Flocculation	150
Sodium Hydroxide 18%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	278
Sodium Hydroxide 20%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	250
Sodium Hydroxide 25%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	200
Sodium Hydroxide 30%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	167
Sodium Hydroxide 33%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	152
Sodium Hydroxide 50%	-	Corrosion and Scale Control, Softening, Sequestering, Precipitation and pH adjustment	100

Chlorine		Disinfection and Oxidation Chemicals	30
Chiorine	-	Distribution and Oxidation Chemicals	30
Sierra Pure Chlor	[HPH]	Disinfection and Oxidation Chemicals	30
Hydrofluosilicic Acid	-	Miscellaneous Treatment Chemicals	6
Hydrochloric Acid			
Hydrochloric Acid 20 Be	-	Corrosion& Scale Control, pH Adjustment	40
Muriatic Acid	-	Corrosion& Scale Control, pH Adjustment	40
Zinc Orthophosphate			
ZO-01 thru ZO-05	[Zn]	Softening, Precipitation, Sequestering, pH adjustment, and Corrosion/Scale Control Chemicals	78
ZO-06 thru ZO-10	[Zn]	Softening, Precipitation, Sequestering, pH adjustment, and Corrosion/Scale Control Chemicals	39
ZO-11 thru ZO-15	[Zn]	Softening, Precipitation, Sequestering, pH adjustment, and Corrosion/Scale Control Chemicals	26
ZO-16 thru ZO-20	[Zn]	Softening, Precipitation, Sequestering, pH adjustment, and Corrosion/Scale Control Chemicals	19

- [AI] The finished drinking water shall be monitored to verify that the level of aluminum does not exceed 2 mg/L.
- [Cu] The finished drinking water shall be monitored to verify that the level of copper does not exceed 1.3 mg/L.
- [HPH] Refer to AWWA B300, "Hypochlorites" for recommended storage and handling practices.
- [PA] Complies with 40 CFR 141.111 requirements for percent monomer and dose when used at or below the MUL.
- [Zn] The finished drinking water shall be monitored to verify that the level of zinc does not exceed 2 mg/L
- [*Al] The finished drinking water shall be monitored to verify that the level of aluminum does not exceed 2 mg/L.
- [*Cu] This chemical contains copper and can increase the amount of copper in the finished drinking water. The finished drinking water shall be monitored to verify that levels of copper do not exceed 1.3 mg/L.
- [*HPH] Refer to AWWA B300, "Hypochlorites" for recommended storage and handling practices.
- [*Mn] The finished drinking water shall be monitored to ensure that levels of manganese do not exceed 0.05 mg/L.
- [*OL] These products are designed to be used off-line and flushed out prior to using the system for drinking water, following the manufacturer's use instructions. The pH or other water chemistry of the influent and effluent water should be monitored to ensure that all traces of the product have been removed before placing into service.
- [*Zn] The finished drinking water shall be monitored to verify that the level of zinc does not exceed 2 mg/L.

Last Updated on 2021-08-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"



CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

UL LLC

333 Pfingsten Road, Northbrook, IL 60062, United States

ACCREDITATION ID#0198

Fulfills the requirements of

ISO/IEC 17065:2012 Conformity assessment - Requirements for bodies certifying products, processes and services

LIST OF CERTIFICATION SCHEME(S)

US Safety Scheme

Food Equipment Sanitation Scheme

Water Systems Scheme

Accredited Elevator/Escalator Certification Organization (AECO): Elevator systems, subsystems, components, and functions for issuance of Certificates of Conformance and Marks according to ASME A17.7/CSA B44.

EPA WaterSense - WaterSense® Product Certification System

This certificate is valid only when accompanied by a current scope of accreditation document. The current scope of accreditation can be verified at www.anab.org.

R. Douglas Leonard Jr., VP, PILR SBU

Expiry Date: 2023-12-01



CHEM

THATCHER COMPANY OF CALIFORNIA, INC.

8625 Unsworth Ave. Sacramento, CA 95828 916-389-2520

PRODUCT SPECIFICATION

Alum (Aluminum Sulfate Solution)

CAS NUMBER: 10043-01-3

CHEMICAL FORMULA: Al₂(SO₄)₃ MOLECULAR WEIGHT: 342.14

PRODUCT DESCRIPTION: Colorless solution free of suspended solids

CERTIFICATIONS: Certified by UL to meet ANSI 60 Standard for Drinking Water

Additives (UL ref.: MH 17003)

Product meets AWWA B-403 Specifications

SPECIFICATIONS: Clarity: Clear with no visible matter present

Color: APHA 20 (max)
Assay: 27.9% as Al₂(SO₄)₃

48.4% as Al₂(SO₄)₃ 14H₂O

8.3% as Al_2O_3

 $\begin{array}{lll} \text{Free Acidity (as H_2SO}_4$) & 0.0\% \text{ (max)} \\ \text{Free Alkalinity (as Al_2O}_3$): & 0.20\% \\ \text{Specific Gravity (20C):} & 1.329\text{-}1.337 \\ \text{Iron (as Fe):} & 50 \text{ ppm (max)} \\ \end{array}$

Arsenic (as As): Non Detect (<0.5 ppm)

Total Heavy Metals (as Pb): 100 ppm (max) Total Halides (as Cl): 500 ppm (max)

CERTIFICATIONS:



ALUMINUM SULFATE ANSI/NSF 60 <35Y2> MUL: 150 mg/L

WARRANTY

This information is, to the best of our knowledge, accurate, but may not be complete. Thatcher Company furnishes this information in good faith, but without warranty, representation or guarantee of its accuracy, completeness or reliability.

1/22/2018

SAFETY DATA SHEET

1. Identification

Product identifier Aluminum Sulfate - Liquid

Other means of identification None.

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Thatcher Company of California, Inc.

Address 8625 Unsworth Avenue

Sacramento, CA 95828

United States

800 (424)-9300

Telephone (916) 389-2520

E-mail inquiries@tchem.com

Emergency phone number

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage.

May cause respiratory irritation. May cause cancer. Toxic to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 72.89% of the mixture consists of component(s) of unknown acute oral toxicity. 73.13% of the

mixture consists of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminum Sulfate		10043-01-3	20 - < 30
Sulfuric acid		7664-93-9	< 0.3
Other components below reportable I	evels		70 - < 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eve contact Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

> Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

equipment/instructions

Specific methods General fire hazards

Fire fighting

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

Wear suitable protective equipment.

Not applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Should not be released into the environment.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

\/_I...

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Sulfuric acid (CAS 7664-93-9)	PEL	1 mg/m3	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
Aluminum Sulfate (CAS 10043-01-3)	TWA	1 mg/m3	Respirable fraction.
Sulfuric acid (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Aluminum Sulfate (CAS 10043-01-3)	TWA	2 mg/m3	
Sulfuric acid (CAS	TWA	1 mg/m3	

Biological limit values

7664-93-9)

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates

No biological exposure limits noted for the ingredient(s).

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye

wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Wash hands after handling and before eating. Keep away from food and drink.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH < 2.4

Material name: Aluminum Sulfate - Liquid

Melting point/freezing point

Limital

Not available.

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability (solid, gas)

Not available.

Not applicable.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.32 - 1.34 g/cm3

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile 72.89 % estimated

Specific gravity 1.32 - 1.34

10. Stability and reactivity

Reactivity Reacts violently with strong alkaline substances. This product may react with reducing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidDo not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Bases. Reducing agents.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Harmful if swallowed. May cause respiratory irritation.

Test Results Components **Species**

Aluminum Sulfate (CAS 10043-01-3)

Acute Oral

LD50 Guinea pig 490 mg/kg

> Mouse > 730 mg/kg Rat 1930 mg/kg

Sulfuric acid (CAS 7664-93-9)

Acute Inhalation

LC50 Guinea pig 0.018 mg/l, 8 Hours Rat

347 mg/l, 1 Hours

Oral

LD50 Rat 2140 mg/kg

Causes severe skin burns and eye damage. Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

May cause cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Sulfuric acid (CAS 7664-93-9) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Sulfuric acid (CAS 7664-93-9) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. Aspiration hazard

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Because of the low pH of this product, it would be expected to produce

significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Species Test Results Components

Aluminum Sulfate (CAS 10043-01-3)

Aquatic

Crustacea EC50 Amphipod (Crangonyx pseudogracilis) 11.8 - 14 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 3.4 - 5.6 mg/l, 96 hours

Sulfuric acid (CAS 7664-93-9)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 42 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN3264 **UN** number

UN proper shipping name Transport hazard class(es) Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum Sulfate RQ = 18608 LBS)

Class 8 Subsidiary risk _ 8 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2, IB2, T11, TP2, TP27

154 Packaging exceptions 202 Packaging non bulk Packaging bulk 242

DOT BULK

BULK

UN number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum Sulfate RQ = 18608 LBS)

Transport hazard class(es)

Class 8 Label(s) 8 Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B2, IB2, T11, TP2, TP27 Special provisions

154 Packaging exceptions 202 Packaging non bulk 242 Packaging bulk

IATA

UN3264 **UN** number

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum Sulfate)

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number UN3264

UN proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Aluminum Sulfate)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group || |

Environmental hazards

Marine pollutant No. EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT; DOT Bulk packaging type



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Aluminum Sulfate (CAS 10043-01-3) Listed. Sulfuric acid (CAS 7664-93-9) Listed.

SARA 304 Emergency release notification

Sulfuric acid (CAS 7664-93-9) 1000 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name **CAS** number Reportable **Threshold** Threshold **Threshold** quantity planning quantity planning quantity, planning quantity, lower value upper value Sulfuric acid 7664-93-9 1000 1000 lbs

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Nο

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Sulfuric acid (CAS 7664-93-9)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Sulfuric acid (CAS 7664-93-9)

6552

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Sulfuric acid (CAS 7664-93-9) 20 %WV

DEA Exempt Chemical Mixtures Code Number

Sulfuric acid (CAS 7664-93-9) 6552

US state regulations

US - New Jersey RTK - Substances: Listed substance

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Sulfuric acid (CAS 7664-93-9)

US. Massachusetts RTK - Substance List

Aluminum Sulfate (CAS 10043-01-3)

Sulfuric acid (CAS 7664-93-9)

US. New Jersey Worker and Community Right-to-Know Act

Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania RTK - Hazardous Substances

Aluminum Sulfate (CAS 10043-01-3)

Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum Sulfate (CAS 10043-01-3)

Sulfuric acid (CAS 7664-93-9)

US. Rhode Island RTK

Aluminum Sulfate (CAS 10043-01-3)

Sulfuric acid (CAS 7664-93-9)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Sulfuric acid (CAS 7664-93-9) Listed: March 14, 2003

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Europe European Inventory of Existing Commercial Chemical

Substances (EINECS)

New Zealand Inventory

Europe European List of Notified Chemical Substances (ELINCS) No

Japan Inventory of Existing and New Chemical Substances (ENCS) Yes

JapanInventory of Existing and New Chemical Substances (ENCS)YesKoreaExisting Chemicals List (ECL)Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 10-22-2018

 Revision date
 11-14-2018

Version # 04

NFPA ratings Health: 3

Flammability: 0 Instability: 0

NFPA ratings

New Zealand



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Alternate Trade Names

Yes

Yes

THATCHER COMPANY OF CALIFORNIA, INC.



8625 Unsworth Ave Sacramento, CA 95828

(916)-389-2520

CERTIFICATE OF ANALYSIS

Alum, Acidified 7

This is to certify that the listed shipment was assayed with the following results:

Lot Number:	
Date of Shipment:	4/12/2021
Customer Name:	
Bill of Lading:	

Parameter	Specification	Result
Appearance:	Slightly opaque liquid, yellow to water white	
Aluminum Oxide	6.0-6.4	
Free Acid	6.8-7.2	



Alum, Acidified 7 ANSI/NSF 60 <35Y2>

MUL: 150 mg/L

Thatcher Company of California, Inc. Authorized Signature

CHEM

THATCHER COMPANY OF CALIFORNIA

8625 Unsworth Ave, Sacramento, CA 95828 (702) 219-2372 PHONE

CERTIFICATE OF ANALYSIS

This is to certify that the listed shipment of Aluminum Sulfate was assayed with the following results:

Lot Number: 2302031077 Analysis Date: 09/21/22

Property	Specification	Result
Total Al ₂ O ₃ (%w/w)	7.8-8.0	8.0
Free Acid (as H ₂ SO ₄ ,%w/w)	0.0	0.0
Free Alumina (%w/w)	None	Pass
Fe ₂ O ₃ (%w/w)	<0.35	Pass
Specific Gravity (15C)	Report	1.315
Insolubles (%w/w)	< 0.2	0.0
Crystals (23C)	None	Pass
Color	Yellow to Water White	Pass
Clarity	Clear to slightly opaque	Pass

Certifications:



ALUMINUM SULFATE ANSI/NSF 60 <35Y2>

Maximum Use Level: 150 mg/L

Authorized Signature: Ames Ettinger

Thatcher Company



THATCHER COMPANY OF CALIFORNIA, INC.

8625 Unsworth Ave. Sacramento, CA 95828 916-389-2520

PRODUCT SPECIFICATION

ALUM, ACIDIFED 7

SYNONYMS: N/A CAS NUMBER: N/A

CHEMICAL FORMULA: N/A MOLECULAR WEIGHT: N/A

PRODUCT DESCRIPTION: Colorless to pale yellow, clear liquid

SPECIFICATIONS:

Appearance: Slightly opaque liquid, yellow to water

white

Assay (as % Al₂O₃): 6.0-6.4 Free Acid (%): 6.8-7.2 Free Al₂O₃ (%): 0 Typ. Specific Gravity (25C): 1.24-1.33 Insoluble Matter (%): <0.2 Iron (% as Fe₂O₃): <0.35 Typ.

CERTIFICATIONS:



Alum, Acidified 7 ANSI/NSF 60 <35Y2> MUL: 150 mg/L

WARRANTY

This information is, to the best of our knowledge, accurate, but may not be complete. Thatcher Company furnishes this information in good faith, but without warranty, representation or guarantee of its accuracy, completeness or reliability.

SAFETY DATA SHEET

1. Identification

Product identifier Alum, Acidified 7%

Other means of identification

Synonyms 2% Acidized Aluminum Sulfate * 5% Acidized Aluminum Sulfate

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Thatcher Company of California, Inc.

Address 8625 Unsworth Avenue

Sacramento, CA 95828

United States

Telephone (916) 389-2520

E-mail inquiries@tchem.com

Emergency phone number 800 (424)-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsAcute toxicity, oralCategory 4Acute toxicity, inhalationCategory 3

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 1

Category 1

Category 1

Category 1

Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Toxic if inhaled. May

cause respiratory irritation. May cause cancer. Harmful to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Rinse mouth. If skin irritation occurs:

Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

 74.12% of the mixture consists of component(s) of unknown acute oral toxicity. 74.12% of the mixture consists of component(s) of unknown acute inhalation toxicity. 79.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	65 - < 80
Aluminum Sulfate		10043-01-3	18 - < 26
Sulfuric acid		7664-93-9	2 - < 11

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Not applicable.

Wear suitable protective equipment.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Alum, Acidified 7%

Methods and materials for containment and cleaning up

Should not be released into the environment.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get this material in contact with eyes. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Sulfuric acid (CAS 7664-93-9)	PEL	1 mg/m3	
US. ACGIH Threshold Limit Value	es		
Material	Туре	Value	Form
Alum, Acidified 7%	TWA	1 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Aluminum Sulfate (CAS 10043-01-3)	TWA	1 mg/m3	Respirable fraction.
Sulfuric acid (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Material	Туре	Value	
Alum, Acidified 7%	TWA	2 mg/m3	
Components	Туре	Value	
Aluminum Sulfate (CAS 10043-01-3)	TWA	2 mg/m3	
Sulfuric acid (CAS 7664-93-9)	TWA	1 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Material name: Alum, Acidified 7%

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear to Slightly Yellow

Physical state Liquid.
Form Liquid.
Color Not available.
Odor threshold Not available.

pH 0.5 - 1.5 100% aqueous solution

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

Reactivity Reacts violently with strong alkaline substances. This product may react with reducing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidDo not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Bases. Reducing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: Alum, Acidified 7%

11. Toxicological information

Information on likely routes of exposure

Toxic if inhaled. Inhalation

Causes skin irritation. Skin contact

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Skin irritation. May cause redness and pain.

Information on toxicological effects

Toxic if inhaled. Harmful if swallowed. May cause respiratory irritation. Acute toxicity

Product	Species	Test Results	
Alum, Acidified 7%			
<u>Acute</u>			
Oral			
LD50	Guinea pig	490 mg/kg	
	Mouse	> 730 mg/kg	
	Rat	1930 mg/kg	
Components	Species	Test Results	
Aluminum Sulfate (CAS 100)43-01-3)		

Acute Oral

LD50 Guinea pig 490 mg/kg

> Mouse > 730 mg/kg Rat 1930 mg/kg

Sulfuric acid (CAS 7664-93-9)

Acute

Inhalation

LC50 Guinea pig 0.018 mg/l, 8 Hours

> Rat 347 mg/l, 1 Hours

Oral

LD50

Rat 2140 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eve damage/eve

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Sulfuric acid (CAS 7664-93-9) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Sulfuric acid (CAS 7664-93-9) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -May cause respiratory irritation.

single exposure

Material name: Alum, Acidified 7% 0111970, 0111950, 0119110, 0115333, 0111910 Version #: 04 Revision date: 03-11-2019 Issue date: 04-26-2016 SDS US

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Harmful to aquatic life. Because of the low pH of this product, it would be expected to produce

significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Components **Species Test Results** Aluminum Sulfate (CAS 10043-01-3)

Aquatic

Crustacea EC50 Amphipod (Crangonyx pseudogracilis) 11.8 - 14 mg/l, 48 hours LC50 Fathead minnow (Pimephales promelas) 3.4 - 5.6 mg/l, 96 hours Fish

Sulfuric acid (CAS 7664-93-9)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 42 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate RQ = 24390 LBS)

Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. IB3, T7, TP1, TP28

Special provisions Packaging exceptions 154 203

Packaging non bulk Packaging bulk 241

DOT BULK

BULK

UN3264 **UN** number

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate RQ = 24390 LBS)

Material name: Alum, Acidified 7%

SDS US

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

8 Class 8 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154 Packaging non bulk 203 Packaging bulk 241

IATA

UN3264 **UN** number

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate)

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. 8L **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed. Cargo aircraft only

IMDG

UN number UN3264

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (aluminum sulfate) UN proper shipping name Transport hazard class(es)

Allowed.

8 **Class** Subsidiary risk Ш Packing group

Environmental hazards

Marine pollutant No. **EmS** F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established. Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

DOT; DOT Bulk packaging type



IATA; IMDG



0111970, 0111950, 0119110, 0115333, 0111910 Version #: 04 Revision date: 03-11-2019 Issue date: 04-26-2016

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Aluminum Sulfate (CAS 10043-01-3) Listed. Sulfuric acid (CAS 7664-93-9) Listed.

SARA 304 Emergency release notification

Sulfuric acid (CAS 7664-93-9) 1000 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name **CAS** number Reportable **Threshold** Threshold **Threshold** planning quantity, quantity planning quantity planning quantity, lower value upper value 1000 1000 lbs Sulfuric acid 7664-93-9

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Sulfuric acid 7664-93-9 2 - < 11

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Sulfuric acid (CAS 7664-93-9)

Clean Water Act (CWA)

Hazardous substance

Section 112(r) (40 CFR

68.130)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Sulfuric acid (CAS 7664-93-9) 6552

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

20 %WV Sulfuric acid (CAS 7664-93-9)

DEA Exempt Chemical Mixtures Code Number

Sulfuric acid (CAS 7664-93-9) 6552

US state regulations

US - New Jersey RTK - Substances: Listed substance

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Sulfuric acid (CAS 7664-93-9)

US. Massachusetts RTK - Substance List

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

Material name: Alum, Acidified 7%

SDS US

0111970, 0111950, 0119110, 0115333, 0111910 Version #: 04 Revision date: 03-11-2019 Issue date: 04-26-2016

US. New Jersey Worker and Community Right-to-Know Act

Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania RTK - Hazardous Substances

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. Rhode Island RTK

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Sulfuric acid (CAS 7664-93-9) Listed: March 14, 2003

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

04-26-2016 Issue date 03-11-2019 **Revision date**

Version #

United States & Puerto Rico

Health: 3 NFPA ratings

Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Yes



THATCHER COMPANY OF CALIFORNIA

8625 Unsworth Ave, Sacramento, CA 95828 (702) 219-2372 PHONE

CERTIFICATE OF ANALYSIS

This is to certify that the listed shipment of Aluminum Sulfate, Acidified, 5 was assayed with the following results:

Lot Number: 220811 Bill of Lading: 277177.

Customer:

Customer PO Numbe.

Manufacture Date: 4/3/20

Analysis Date: 4/10/20

Trailer Number:

Trailer Seal 1: 366007
Trailer Seal 2: E366006

Property	Specification	Result
Total Al ₂ O ₃ (%w/w)	6.0-6.4	6.04
Total H ₂ SO ₄ (%w/w)	4.8-5.2	5.18
Free Alumina (%w/w)	None	PASS
Fe ₂ O ₃ (%w/w)	<0.35	DWI
Specific Gravity	1.24-1.33	1.25
Insolubles (%w/w)	< 0.2	PMS
Color	Yellow to Water White	PATS
Clarity	Clear to slightly opaque	6 WZZ

Certifications:

WATER QUALITY

ALUMINUM SULFATE, ACIDIFIED 5% ANSI/NSF 60 <35Y2>

Authorized Signature:

Thatcher Company



THATCHER COMPANY OF CALIFORNIA, INC.

8625 Unsworth Ave. Sacramento, CA 95828 916-389-2520

PRODUCT SPECIFICATION

Aluminum Sulfate, Acidified 5%

SYNONYMS: 5% Acidized Aluminum Sulfate

CAS NUMBER: 10043-01-3 CHEMICAL FORMULA: Al₂(SO₄)₃ MOLECULAR WEIGHT: 342.14

PRODUCT DESCRIPTION: Colorless solution free of suspended solids

SPECIFICATIONS: Clarity: Slightly opaque liquid

yellow to water white with no visible

solids

Assay: 6.0-6.4% as Al₂O₃

Free Acidity (as H_2SO_4) 4.8-5.2%

CERTIFICATIONS:



ALUM, ACIDIFIED X [*AI]
ANSI/NSF 60
<35Y2>
MUL: 150 mg/L

WARRANTY

This information is, to the best of our knowledge, accurate, but may not be complete. Thatcher Company furnishes this information in good faith, but without warranty, representation or guarantee of its accuracy, completeness or reliability.

1/31/2018

CHEM

THATCHER COMPANY OF CALIFORNIA

8625 Unsworth Ave, Sacramento, CA 95828 (702) 219-2372 PHONE

CERTIFICATE OF ANALYSIS

This is to certify that the listed shipment of Aluminum Sulfate, Acidified, 5 was assayed with the following results:

Lot Number: **2301241083**

Bill of Lading: Customer:

Customer PO Number

 Manufacture Date:
 01/31/23

 Analysis Date:
 01/31/23

 Trailer Number:
 T308

 Trailer Seal 1:
 F0418514

 Trailer Seal 2:
 F0418513

Property	Specification	Result
Total Al ₂ O ₃ (%w/w)	6.0-6.4	6.2
Total H ₂ SO ₄ (%w/w)	4.8-5.2	4.8
Free Alumina (%w/w)	None	Pass
Fe ₂ O ₃ (%w/w)	<0.35	Pass
Specific Gravity	1.24-1.33	1.28
Insolubles (%w/w)	< 0.2	Pass
Color	Yellow to Water White	Pass
Clarity	Clear to slightly opaque	Pass

Certifications:



ALUMINUM SULFATE, ACIDIFIED 5% ANSI/NSF 60 <35Y2>

Authorized Signature:

Ames Ettinger

Thatcher Company

SAFETY DATA SHEET

1. Identification

Product identifier Alum, Acidified 5%

Other means of identification

Synonyms 2% Acidized Aluminum Sulfate * 5% Acidized Aluminum Sulfate

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Thatcher Company of California, Inc.

Address 8625 Unsworth Avenue

Sacramento, CA 95828

United States

Telephone (916) 389-2520

E-mail inquiries@tchem.com

Emergency phone number 800 (424)-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, inhalation

Category 3

Skin corrosion/irritation

Category 1

Serious eye damage/eye irritation

Category 1

Carcinogenicity

Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Toxic if inhaled. May

cause respiratory irritation. May cause cancer. Harmful to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Rinse mouth. If skin irritation occurs:

Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: Alum, Acidified 5% 0111970, 0111950, 0119110, 0115333, 0111910 Version #: 03 Revision date: 03-31-2017 Issue date: 04-26-2016

74.12% of the mixture consists of component(s) of unknown acute oral toxicity. 74.12% of the mixture consists of component(s) of unknown acute inhalation toxicity. 79.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	65 - < 80
Aluminum Sulfate		10043-01-3	18 - < 26
Sulfuric acid		7664-93-9	2 - < 11

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Skin irritation. May cause redness and pain.

Get medical advice/attention if you feel unwell.

symptoms/effects, acute and

Most important

General information

delayed

Indication of immediate medical attention and special Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

treatment needed

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Not applicable.

Wear suitable protective equipment.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

General fire hazards No unusual fire or explosion hazards noted.

Specific methods

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Use standard firefighting procedures and consider the hazards of other involved materials.

Material name: Alum, Acidified 5%

Methods and materials for containment and cleaning up

Should not be released into the environment.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get this material in contact with eyes. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Sulfuric acid (CAS 7664-93-9)	PEL	1 mg/m3	
US. ACGIH Threshold Limit Values			
Material	Туре	Value	Form
Alum, Acidified 5%	TWA	1 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Aluminum Sulfate (CAS 10043-01-3)	TWA	1 mg/m3	Respirable fraction.
Sulfuric acid (CAS 7664-93-9)	TWA	0.2 mg/m3	Thoracic fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Material	Туре	Value	
Alum, Acidified 5%	TWA	2 mg/m3	
Components	Туре	Value	
Aluminum Sulfate (CAS 10043-01-3)	TWA	2 mg/m3	
Sulfuric acid (CAS 7664-93-9)	TWA	1 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

0111970, 0111950, 0119110, 0115333, 0111910 Version #: 03 Revision date: 03-31-2017 Issue date: 04-26-2016

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear to Slightly Yellow

Physical state Liquid.
Form Liquid.
Color Not available.
Odor Not available.
Odor threshold Not available.

pH 0.5 - 1.5 100% aqueous solution

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityReacts violently with strong alkaline substances. This product may react with reducing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Bases. Reducing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: Alum, Acidified 5%

11. Toxicological information

Information on likely routes of exposure

Toxic if inhaled. Inhalation

Causes skin irritation. Skin contact

Eve contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Skin irritation. May cause redness and pain.

Information on toxicological effects

Toxic if inhaled. Harmful if swallowed. May cause respiratory irritation. Acute toxicity

Product	Species	Test Results	
Alum, Acidified 5%			
<u>Acute</u>			
Oral			
LD50	Guinea pig	490 mg/kg	
	Mouse	> 730 mg/kg	
	Rat	1930 mg/kg	
Components	Species	Test Results	

Acute Oral

LD50 Guinea pig 490 mg/kg

> Mouse > 730 mg/kg Rat 1930 mg/kg

Sulfuric acid (CAS 7664-93-9)

Acute

Inhalation

LC50 Guinea pig 0.018 mg/l, 8 Hours

Rat 347 mg/l, 1 Hours

Oral LD50

Rat 2140 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eve damage/eve

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Sulfuric acid (CAS 7664-93-9) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Sulfuric acid (CAS 7664-93-9) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -May cause respiratory irritation.

single exposure

Material name: Alum, Acidified 5% 0111970, 0111950, 0119110, 0115333, 0111910 Version #: 03 Revision date: 03-31-2017 Issue date: 04-26-2016

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Harmful to aquatic life. Because of the low pH of this product, it would be expected to produce

significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

Components **Species Test Results**

Aluminum Sulfate (CAS 10043-01-3)

Aquatic

Crustacea EC50 Amphipod (Crangonyx pseudogracilis) 11.8 - 14 mg/l, 48 hours LC50 Fathead minnow (Pimephales promelas) 3.4 - 5.6 mg/l, 96 hours Fish

Sulfuric acid (CAS 7664-93-9)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 42 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate RQ = 24390 LBS)

Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154 Packaging non bulk 203 Packaging bulk 241

DOT BULK

BULK

UN3264 **UN** number

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate RQ = 24390 LBS)

Material name: Alum, Acidified 5% 0111970, 0111950, 0119110, 0115333, 0111910 Version #: 03 Revision date: 03-31-2017 Issue date: 04-26-2016

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

8 Class 8 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154 Packaging non bulk 203 Packaging bulk 241

IATA

UN3264 **UN** number

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s. (aluminum sulfate)

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. 8L **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed. Cargo aircraft only

Ш

Allowed.

IMDG

UN number UN3264

UN proper shipping name Transport hazard class(es) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (aluminum sulfate)

8 **Class** Subsidiary risk

Packing group **Environmental hazards**

Marine pollutant No.

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT; DOT Bulk packaging type



IATA; IMDG



Material name: Alum, Acidified 5%

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Aluminum Sulfate (CAS 10043-01-3) Listed. Sulfuric acid (CAS 7664-93-9) Listed.

SARA 304 Emergency release notification

Sulfuric acid (CAS 7664-93-9) 1000 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name **CAS** number Reportable **Threshold** Threshold **Threshold** planning quantity, quantity planning quantity planning quantity, lower value upper value 1000 lbs

1000 Sulfuric acid 7664-93-9

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Sulfuric acid 7664-93-9 2 - < 11

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Sulfuric acid (CAS 7664-93-9)

Clean Water Act (CWA)

Hazardous substance

Section 112(r) (40 CFR

68.130)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Sulfuric acid (CAS 7664-93-9)

6552

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

20 %WV Sulfuric acid (CAS 7664-93-9)

DEA Exempt Chemical Mixtures Code Number

Sulfuric acid (CAS 7664-93-9) 6552

US state regulations

US - New Jersey RTK - Substances: Listed substance

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Sulfuric acid (CAS 7664-93-9)

US. Massachusetts RTK - Substance List

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

Material name: Alum, Acidified 5% 0111970, 0111950, 0119110, 0115333, 0111910 Version #: 03 Revision date: 03-31-2017 Issue date: 04-26-2016 SDS US

US. New Jersey Worker and Community Right-to-Know Act

Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania RTK - Hazardous Substances

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. Rhode Island RTK

Aluminum Sulfate (CAS 10043-01-3) Sulfuric acid (CAS 7664-93-9)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Sulfuric acid (CAS 7664-93-9) Listed: March 14, 2003

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

04-26-2016 Issue date 03-31-2017 **Revision date**

Version # 03

United States & Puerto Rico

NFPA ratings Health: 3

Flammability: 0 Instability: 0

NFPA ratings



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

> information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Synonyms

Material name: Alum, Acidified 5%

Yes

THATCHER COMPANY OF CALIFORNIA, INC.

8625 Unsworth Avenue, Sacramento, CA 95828



Phone (916) 389-2517 Fax (916) 389-2516

MAILING ADDRESSES

Address Then E-mail Contracts & Agreements To:

Thatcher Company of California, Inc. Attn: Craig N. Thatcher, C.E.O. P. O. Box 27407

Salt Lake City, UT 84127-0407

craig.thatcher@tchem.com and wendy.richmond@tchem.com

Address Then E-mail Requests For Bids & Quotations To:

Thatcher Company of California, Inc. Attn: Craig N. Thatcher, C.E.O.

P. O. Box 27407

Salt Lake City, UT 84127-0407 wendy.richmond@tchem.com

Mail Payment: Thatcher Company of California, Inc.

LB 1106

P. O. Box 35146

Seattle, WA 98124-5146

Order Placement: Customer Service (916) 389-2517 csca@tchem.com

24/7 Customer & Transportation Service: (800) 375-7758

E-mail Requests For Certificate of Insurance: wendy.richmond@tchem.com

Bid Tabulation: wendy.richmond@tchem.com

zach.brackus@tchem.com